



DURA.PC třetinový žlab

| Specifikace | Stavební délka | Rozměry |       |    |       |       | Hmotnost | Množství/bal. |
|-------------|----------------|---------|-------|----|-------|-------|----------|---------------|
| Koryto      | $l_1$          | s       | $h_1$ | d  | $b_1$ | $b_2$ |          |               |
| DN          | mm             | mm      | mm    | mm | mm    | mm    | kg/ks    | ks            |
| 200         | 495            | 13,00   | 50    | 18 | 173   | 60    | 4,50     | 80            |
| 250         | 495            | 12,50   | 63    | 18 | 217   | 60    | 5,50     | 80            |
| 300         | 495            | 12,50   | 75    | 18 | 260   | 80    | 6,50     | 80            |
| 350         | 495            | 13,00   | 87    | 18 | 303   | 80    | 7,50     | 80            |
| 400         | 495            | 13,00   | 100   | 18 | 346   | 80    | 9,50     | 60            |
| 450         | 495            | 13,00   | 113   | 18 | 390   | 80    | 12,50    | 52            |
| 500         | 495            | 20,00   | 125   | 20 | 433   | 80    | 14,00    | 44            |
| 550         | 495            | 20,00   | 138   | 20 | 476   | 80    | 25,00    | 30            |
| 600         | 495            | 20,00   | 150   | 20 | 520   | 80    | 18,00    | 36            |
| 700         | 495            | 22,00   | 175   | 22 | 606   | 80    | 18,50    | 36            |

Tolerance dle normy EN 14636