



## DURA.PC Kineta

| Specyfikacja | Długość konstrukcyjna | Wymiary |       |    |       |       | Ciężar  | Ilość / PU |
|--------------|-----------------------|---------|-------|----|-------|-------|---------|------------|
| Kanał        | $l_1$                 | s       | $h_1$ | d  | $b_1$ | $b_2$ |         |            |
| DN           | mm                    | mm      | mm    | mm | mm    | mm    | kg/szt. | Szt.       |
| 150          | 1000                  | 18,00   | 75    | 18 | 151   | 115   | 13,00   | 50         |
| 200          | 1000                  | 20,00   | 100   | 20 | 201   | 150   | 20,00   | 40         |
| 250          | 1000                  | 20,00   | 125   | 20 | 251   | 185   | 23,00   | 30         |
| 300          | 1000                  | 20,00   | 150   | 20 | 302   | 195   | 25,00   | 26         |
| 350          | 1000                  | 20,00   | 175   | 20 | 350   | 230   | 34,00   | 24         |
| 400          | 1000                  | 20,00   | 200   | 20 | 401   | 200   | 33,50   | 12         |
| 500          | 1000                  | 20,00   | 250   | 20 | 501   | 330   | 43,00   | 8          |
| 600          | 1000                  | 20,00   | 300   | 20 | 601   | 300   | 52,00   | 9          |
| 700          | 1000                  | 20,00   | 350   | 20 | 700   | 300   | 55,00   | 7          |
| 800          | 1000                  | 21,00   | 400   | 21 | 800   | 305   | 68,00   | 7          |
| 1000         | 1000                  | 22,00   | 500   | 22 | 1000  | 305   | 85,00   | 3          |

Tolerancje zgodnie z normą EN 14636